



Product ID: **IC-712-I**

Product Name: **2 Ports PS2
KVM Switch**

Features

- Controls PCs with one PS/2 keyboard, PS/2 mouse and monitor respectively
- Supports the standard PS/2 mouse, Microsoft IntelliMouse (PS/2 compatible/Optical/Explorer 3.0), WheelMouse Optical, Trackball (Optical 1.0/Explorer 1.0) & Logitech TrackMan (Marble/Marble FX/Marble+), Cordless MouseMan (Wheel/Optical), Cordless TrackMan (FX/Live) mouse, Cordless Optical TrackMan, MX300 Optical mouse. MX300 Optical mouse
- Fully supports the Microsoft IntelliPoint 5.0 mouse driver & Logitech Mouse Ware driver
- Supports the Windows 95/98/98SE/Me/NT4.0/2000/XP, DOS, Linux, Novell Netware, FreeBSD
- Superior video quality - Up to 1920 x 1440, DDC, DDC2, DDC2B, DDC2AB, 200MHz
- Real mouse identification function
- 2 ways for PC selection - Push-button switch or hot key
- Easy to install - No software required
- Hot Pluggable
- Integral keyboard and mouse emulation for PC booting error free
- Auto scan function to monitor PCs
- Auto skips over the power-off PC
- Beep sound and multi selection ways on/off option for port selection

Package

- 1 Smart View IC-712-I KVM Switch.
- 1 User Manual.

Hardware Require

- **Console**
One highest resolution VGA, SVGA or Multisync monitor. One PS/2 Mouse. One PS/2 Keyboard.

- **PC**
One VGA, SVGA or Multisync card. One 6-pin mini-DIN (PS/2) mouse port. One 6-pin mini-DIN (PS/2) keyboard port.
- **Cable**
Smart View Custom Cable (3L-1618C or 3L-1630C) or Equivalent.

Specification

PC Connections	2
Port Selection	Push-button Switch / Hot Key
LED	
On Line	2
Selected	2
Emulation	
Keyboard	PS/2
Mouse	PS/2
Console Connector	
Keyboard	1x6 pin mini-DIN Female (PS/2)
Mouse	1x6 pin mini-DIN Female (PS/2)
Monitor	1 HD-15 Female(Std. VGA/SVGA)
CPU Connector	
Keyboard	2x6 pin mini-DIN Female (PS/2)
Mouse	2x6 pin mini-DIN Female (PS/2)
Monitor	2 HD-15 Male(Std. VGA/SVGA)
VGA Resolution	1920x1440 (Max.); DDC; DDC2; DDC2B; DDC2AB; 200MHz
DC Power Adaptor	
Voltage	9V (Spare)
Amps	300mA (Min.)
Scan Interval	5 sec ~ 30 sec
Housing	Metal
Weight	420g
Dimensions	
Length	128mm
Width	75mm
Height	45mm