



## NR0001 TL-R402M

### Spotlight

- Cable/DSL Router for home, Build-in 4-port Switch
- Share data and Internet access

## Inquire Now

### Description

The TL-R402M Multifunctional Broadband Router is specially designed for small enterprise, office and SOHO (Small Office/Home Office) to access the Internet. It features strong functions, high performance, and easy configuration router. The TL-R402M provides many management functions, including system, DHCP server, virtual server, DMZ host, firewall, and static routing table.

The TL-R402M router provides flexible access control, limiting staff or children to browse selected sites. It connects to the Internet automatically or on demand and disconnects when idle to save on network costs. Quick Setup Wizard is supported and friendly help pages are provided for every step.

### Features

- Complies with IEEE802.3, IEEE802.3u standards
- 1 10/100Mbps Auto-Negotiation WAN RJ45 port, supporting Auto-MDI/MDIX
- 4 10/100Mbps Auto-Negotiation LAN ports, supporting Auto-MDI/MDIX
- Shares data and Internet access for Stations, connecting Internet through PPPoE on demand and disconnecting when idle
- Supports TCP/IP, PPPoE, DHCP, ICMP, NAT
- Built-in NAT and DHCP server supporting static IP address distributing
- Built-in Firewall supporting Domain Name filtering, and MAC address filtering
- Supports Virtual Server, Special Application, and DMZ host
- Supports Static Routing, VPN pass-through
- Supports firmware upgrade, Remote and Web management

### Specifications

Standards	IEEE 802.3; IEEE 802.3u
Ethernet Protocol	CSMA/CD
Ports	WAN: 1 10/100 Auto-MDI/MDIX RJ-45 Port LAN: 4 10/100 Auto-MDI/MDIX RJ-45 Ports
Application Protocols	TCP/IP, PPPoE, DHCP, NAT

Flow Control	IEEE802.3x for Full duplex Backpressure for Half duplex
LEDs	M1, M2 WAN: Link/Act LAN: Link/Act
Power	External, 9V ~ 0.8A
Operating Temp.	0°C ~ 40°C
Operating Humidity	5% ~ 90%RH, Non-Condensing
Safety & Emission	FCC, CE
Dimension (W;ÁD;ÁH)	6.2 x 4.3 x 1.3 in.(158 x 110 x 32 mm)