

LogiLink®



Art No. WC0007

Pan & Tilt IP Camera 802.11n wireless

Features

- CPU+DSP+RF: Prolific PL-1029 + RL 802.11n
- RAM: 32MB SDRAM
- Flash: 4MB Flash
- Image Sensor: Micron MI-1320 1.3M Pixels CMOS Sensor
- Lens: 5 mm, Manual Focus, F=2.8
- LAN Port: 10/100M UTP Port x 1
- WLAN 802.11b/g/n
- Cardreader Slot: SD, SDHC
- Power: 12V DC, 1A Power Adaptor
- Dimension: 108mm x 112mm x 108mm
- Temperature: 0~45oC
- Humidity: 10~90% (Non-Condensing)
- Certification: FCC Class B, CE Mark
- Firmware Upgradeable
- Dual Mode: MPEG4 and Motion-JPEG Image Video
- Multiple Profile: Output M-JPEG and MPEG4 in the same time
- Multi-area motion detection
- Web UI Remote Pan-Tilt Control
- Support SD card for local recording
- Event Trigger: Mail & FTP
- 2-way audio
- High Speed Hardware-Based Image Compression
- Auto sending Snapshot to E-mail and FTP
- Multiple cameras simultaneously up to 16 at a time

www.LogiLink.com