



Art No. WC0015

Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Feature:


- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768(H) x 494(V), PAL: 752(H) x 582(V)
- MPEG4, MJPEG and H.264 compression
- Smart Zoom: zoom in on the object that triggered the alarm
- True Day & Night surveillance with IR shifter & large aperture lens (F1.8)
- Vari-focal Lens f4.0mm ~ f9.0mm, View: 75° ~ 36°
- Outdoor IP Rating with IP67
- Longer IR effective distance up to 40 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Durable 56 IR LEDs built-in application
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time

Specification:

• Environment	
In/Out door use	Outdoor
Day/Night	Yes
• Network	
LAN Port	YES
LAN Connection	10/100 Based-T Ethernet
Frame Rate	NTSC: 30, PAL: 25

Remark: For 3G Mobile Phone Surveillance, please download the mobile software installation for remote Surveillance via Mobile Phone or PDA from www.logilink.com.

* The specifications and pictures are subject to change without notice.
*All trade names referenced are the registered namework of their respective owners.



Made in Taiwan



Art No. WC0015

Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens


Specification:

Number of Online Users	10
Network	With 3G Mobile Phone Surveillance
• Video	
Video Compression	H.264 / MPEG4 / MJPEG
Video Remote Control	YES
Video Adjustment	Brightness, Contrast, Saturation and Hue
• Camera	
Image Sensor	1/3" HR color CCD image sensor
Pixels	NTSC: 768(H) x 494(V) / PAL: 752(H) x 582(V)
Min Illumination	0.05 Lux / F1.4, 0 Lux (IR ON)
Shutter Speed	1/60 (1/50) to 1/100,000 sec.
Lens	2.25x Zoom F1.8/f4.0mm~f9.0mm
Viewing Angle	75° ~ 36°
IR LED	56 units
IR Effective Range	Up to 40 meters
IR Shift	YES
Smart Light Control	YES
Smart Zoom	YES
Auto Tracking	YES
BLC	On/Off
White Balance	ATW
AGC	Auto
IRIS Mode	AI / AES
IP Rating	IP67

* The specifications are subject to change without notice.

** Dimensional tolerance: (± 5mm)

* The specifications and pictures are subject to change without notice.
** All trade names referenced are the registered trademark of their respective owners.



Made in Taiwan




Art No. WC0015

Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Specification:

• Software	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Security	Multiple user access levels with password protection
Web Management	The licensed software "Video Viewer" for up to 16 network cameras control simultaneously
Remote Control	YES
Motion Detection	YES
Alarm and event Notification	Image upload over FTP and Email
Mobile	Supports 3GPP mobile surveillance
• Others	
Power Source (±10%)	AC100V ~ 240V
Operating Temp.	-20°C~40°C
Minimum Web Browsing Requirements:	- Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD - 256 MB RAM - AGP graphics card, Direct Draw, 32MB RAM - Windows 7, Vista, XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later - Internet Explorer 6.x or later
Dimensions (mm)**	282.4(L) x 117.89(W) x 212.63(H)

* The specifications and pictures are subject to change without notice.
**All trade names referenced are the registered namework of their respective owners.



Made in Taiwan



Art No. WC0015

Outdoor IR IP Camera, H.264, with Optical Smart Zoom & Vari-focal Lens

Package contents

- 1 x Outdoor IR IP Camera
- 1 x RJ-45 Network Cable
- 1 x Bracket
- 1 x CD-ROM disc for user manual & licensed software "Video Viewer"

Note:


- The DC12V 1A adapter & power cord are not included with the sales package. Please prepare yourself or order if necessary.

Packaging Information:

- Packing Dimension: 405x164x246 mm
- Packing Weight: 2.3kg
- Carton Dimension: 428x355x522 mm
- Carton Q'ty: 4pcs
- Carton Weight: 9.46kgs



* The specifications and pictures are subject to change without notice.
* All trade names referenced are the registered trademark of their respective owners.



Made in Taiwan